

Scotch® Photoelectric Scanning Tape 7800



Technical Data

May, 2003

Product Description

Scotch® Photoelectric Scanning Tape 7800 is an exposed-lens retroreflective tape with a pressure-sensitive adhesive that is designed for use as expendable code marks in automatic warehouse or conveyor operations. This product affords exceptional contrast with its background for increased accuracy, reliability, and depth-of-field in photoelectric sorting and classification systems and may be employed with automatic on-line applicators or manual dispensers for identification or simple sortation of paperboard shipping containers.

Construction

Color	Lens	Liner
Medium gray	Exposed	None

Typical Physical Properties

Note: The following technical information and data should be considered representative or typical only, and should not be used for specification purposes.

Thickness	
Applied:	.007 in. (.017 cm)
Typical Luminance Factor	
-4° reading:	200X
Skewed 45° reading:	100X
Temperature Resistance	
Continuous exposure:	350°F (177°C)
Intermittent exposure (30 min.):	500°F (260°C)

Features

- Lower price.
- Sticks to various surfaces.
- Accurate and reliable photoelectric sorting.
- Worry-free performance.
- Suitable for high volume.

Available Sizes

Available Widths	Available Lengths
1/2 in. (1.27 cm), 3/4 in. (1.90 cm), 1 in. (2.54 cm), 2 in. (5.08 cm)	50 yds. (45.7 m)
1/2 in. (1.27 mm)	200 yds. (183 m)

Custom widths and lengths available on request, subject to minimum order requirements.

Scotch® Photoelectric Scanning Tape

7800

Application Techniques Automatic and manual dispensers are available to facilitate application of retroreflective tapes.

Application should be made above 50°F (10°C), on a clean and dry surface. After application, Scotch® Photoelectric Scanning Tape 7800 will withstand a continuous ambient temperature of 350°F (177°C).

These materials are designed for use in a relatively dry environment. Reflective quality will deteriorate if the reflective surface is contaminated with moisture, water, oil, solvents, etc.

Storage Conditions Store in a cool, dry area, preferably at 70-75°F (20-24°C) and 30-50% relative humidity, and horizontally in shipping carton. Avoid pressure from stacking.

Shelf Life Product should be applied within one year after purchase.

For Additional Information To request additional product information or to arrange for sales assistance, call toll free 1-800-362-3550 or visit www.3M.com/packaging. Address correspondence to: 3M Industrial Adhesives and Tapes Division, Building 21-1W-10, 900 Bush Avenue, St. Paul, MN 55144-1000. Our fax number is 651-778-4244. In Canada, phone: 1-800-364-3577. In Puerto Rico, phone: 1-787-750-3000. In Mexico, phone: 52-70-04-00.

Important Notice 3M MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. Please remember that many factors can affect the use and performance of a 3M product in a particular application. The materials to be bonded with the product, the surface preparation of those materials, the product selected for use, the conditions in which the product is used, and the time and environmental conditions in which the product is expected to perform are among the many factors that can affect the use and performance of a 3M product. Given the variety of factors that can affect the use and performance of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's application.

Limitation of Remedies and Liability If the 3M product is proved to be defective, THE EXCLUSIVE REMEDY, AT 3M'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE 3M PRODUCT. 3M shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental, or consequential, regardless of the legal theory asserted, including, but not limited to, contract, negligence, warranty, or strict liability.

ISO 9002

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9002 standards.

3M

**Industrial Business
Industrial Adhesives and Tapes Division**
3M Center, Building 21-1W-10, 900 Bush Avenue
St. Paul, MN 55144-1000



Recycled Paper
40% pre-consumer
10% post-consumer

Printed in U.S.A.
©3M 2003 70-0710-0280-5 (5/03)