

Scotch® Filament Tape 890C



Technical Data

April, 2003

Product Description

Scotch® Filament Tape 890C is a high performance black packaging tape reinforced with continuous glass yarn filaments which give the tape very high tensile strength. The black 3M™ Scotchpar™ backing provides outdoor weathering, abrasion, moisture, and scuff resistance. The adhesive is an aggressive packaging adhesive specifically formulated to provide balanced performance, having both high adhesion and long term holding power.

Construction

Backing	Adhesive	Reinforcement	Backing Color
Black 3M™ Scotchpar™ film	Pressure sensitive rubber resin	Glass yarn	Black

Typical Physical Properties

Note: The following technical information and data should be considered representative or typical only, and should not be used for specification purposes.

		ASTM Test Method
Adhesion to Steel:	50 oz./in. width (54 N/100 mm width)	D-3330
Tensile Strength:	600 lbs./in. width (10,500 N/100 mm width)	D-3759
Elongation at Break:	3%	D-3759
Total Thickness:	8.0 mil (0.202 mm)	D-3652

Features

- Meets ASTM D5330, Type IV (replaces PPP-T-97E).
- Protects tape from sunlight and ultra violet rays.
- Good handling.
- Printable by the print seal process.
- High shear strength.
- Good initial adhesion.
- Excellent aging before and after application.
- Excellent protection of filaments and adhesive to provide longer package life.
- Maximizes package performance when exposed to outdoor and humid environments.
- Saves time through ease of dispensing and handling versus glue and strapping.
- Low unit cost on applications where high tensile strength is main requirement by using less tape.

Scotch® Filament Tape

890C

Available Sizes	Standard Widths:	.47 in. (12 mm), .71 in. (18 mm), .94 in. (24 mm)
	Core Size (ID):	3 in. (76.2 mm)
	Lengths:	60 yds. (55 m)

Application Techniques An extensive line of application equipment including hand-held dispensers and an automatic L-Clip applicator is available. Application is most easily accomplished at room temperature. At lower temperatures, approaching 32°F (0°C), the adhesive becomes firm. Once applied, Scotch® Filament Tape 890C performs well throughout the normal temperature ranges encountered by packaged products in shipping and storage environments, even when exposed to moderate amounts of sunlight.

Storage Conditions Store behind present stock. Store in a clean, dry place. Temperature of 40-80°F (4-26°C) and 40-50% relative humidity are recommended. Rotate your stock.

For Additional Information To request additional product information or to arrange for sales assistance, call toll free 1-800-362-3550 or visit www.3M.com/packaging. Address correspondence to: 3M Industrial Adhesives and Tapes Division, Building 21-1W-10, 900 Bush Avenue, St. Paul, MN 55144-1000. Our fax number is 651-778-4244. In Canada, phone: 1-800-364-3577. In Puerto Rico, phone: 1-787-750-3000. In Mexico, phone: 52-70-04-00.

Important Notice 3M MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. Please remember that many factors can affect the use and performance of a 3M product in a particular application. The materials to be bonded with the product, the surface preparation of those materials, the product selected for use, the conditions in which the product is used, and the time and environmental conditions in which the product is expected to perform are among the many factors that can affect the use and performance of a 3M product. Given the variety of factors that can affect the use and performance of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's application.

Limitation of Remedies and Liability If the 3M product is proved to be defective, THE EXCLUSIVE REMEDY, AT 3M'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE 3M PRODUCT. 3M shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental, or consequential, regardless of the legal theory asserted, including, but not limited to, contract, negligence, warranty, or strict liability.



This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9002 standards.



Industrial Business
Industrial Adhesives and Tapes Division
3M Center, Building 21-1W-10, 900 Bush Avenue
St. Paul, MN 55144-1000



Recycled Paper
40% pre-consumer
10% post-consumer

Printed in U.S.A.
©3M 2003 70-0710-0269-8 (4/03)