



ScotchPad™

Custom Carry Handle (8329)

8329

Technical Data

March, 2006

Product Description

3M™ ScotchPad™ Carry Handle 8329 is made of durable plastic strips with adhesive at each end. The ScotchPad Custom Carry Handle 8329 is available in white or with custom printed or colored carry portion material. It is easy to create a convenient looped handle when the ends are attached to both sides of a box or package.

Construction

Backing:	Available in custom backing.
Adhesive:	Pressure-sensitive rubber resin. Requires no heat, moisture or solvent activation prior to use.
Carry Portion Material (CPM):	White or colored paper. Available custom printed.

Typical Physical Properties

Note: The following technical information and data should be considered representative or typical only, and should not be used for specification purposes.

		ASTM Test Method
Adhesion to Steel:	60-100 oz./in. width*	D-3330
Tensile Strength:		
Longitudinal-	150-270 lbs./in. width*	D-3759
Elongation at Break:	10-30%*	D-3759
Thickness:		D-3652
Tape	Various*	
Carry Portion Material	”	
Total	”	
Shelf Life:	18 months when stored in accordance with “Storage Conditions” on page 2.	


*Based on custom construction.

Features

- Adhesive handle.
- High-performance carrying tape.
- Custom colors and graphics.
- Compact size.
- Easy to carry bulky packages.
- Excellent adhesion.
- Easy to apply.
- Easy package identification.
- Captures customers attention.
- Promotion/communications vehicle.
- Customer convenience.
- Carry more items.
- Adheres to a variety of surfaces.
- Speeds up customer traffic through checkout lines.
- In-store security.
- Stores easily at checkout counter.
- Reduces packaging/waste.
- Increases brand awareness.

3M™ ScotchPad™ Custom Carry Handle (8329) 8329

Handle Dimensions



Application Ideas

- Carrying bulky products up to 50 lbs. (small appliances, small electronics, toys, lawn, garden, heavy houseware and hardware items) some industrial products and bulk packaged items.
- Combining products while using a handle (shrink wrapped multipacks).
- Providing special promotional messages or UPC codes on the handle.

Storage Conditions

Prior to use, storage of handles at 70°F (21°C) and 40-50% relative humidity is recommended.

Product Use

All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

Warranty and Limited Remedy

Unless stated otherwise in 3M's product literature, packaging inserts or product packaging for individual products, 3M warrants that each 3M product meets the applicable specifications at the time 3M ships the product. Individual products may have additional or different warranties as stated on product literature, package inserts or product packages. 3M MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. If the 3M product is defective within the warranty period, your exclusive remedy and 3M's and seller's sole obligation will be, at 3M's option, to replace the product or refund the purchase price.

Limitation of Liability

Except where prohibited by law, 3M and seller will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

ISO 9001:2000

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001:2000 standards.



Industrial Business Industrial Adhesives and Tapes Division

3M Center, Building 21-1W-10, 900 Bush Avenue
St. Paul, MN 55144-1000
800-362-3550 • 877-369-2923 (fax)
www.3M.com/industrial



Recycled Paper
40% pre-consumer
10% post-consumer

Printed in U.S.A.
©3M 2006 70-0710-0343-1 (3/06)