



Transparent Polyester/Silicone Tape

8911

Technical Data

September, 2003

Product Description 3M™ Polyester/Silicone Tape 8911 is a transparent high temperature polyester tape with a silicone adhesive for use in composite bonding, splicing and other polyester tape applications requiring transparent tape.

Product Construction	Backing	Adhesive	Color	Standard Roll Length
	Polyester	Silicone	Transparent	72 yds. (66 m) unlined 216 yds. (198 m) lined

Typical Physical Properties

Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

		ASTM Test Method
Adhesion to Steel:	30 oz./in. width (33 N/100 mm)	D-3330
Tensile Strength at Break	30 lbs./in. width (525 N/100 mm)	D-3759
Elongation at Break:	100%	D-3759
Backing Thickness:	1 mil (0.03 mm)	D-3652
Total Tape Thickness: (excluding liner)	2.8 mils (0.07 mm)	D-3652
Temperature Use Range:	Up to 425°F (218°C)	

Features

- Designed to provide clean removal during masking operations involving high temperatures and pressure.
- Polyester film retains flexibility and thermal resistance to help reduce failures due to cracking.
- Abrasion, chemical and thermal resistance to help reduce failures due to backing deterioration.
- Silicone adhesive helps reduce failure due to softening, oozing, and adhesive transfer.

3M™ Transparent Polyester/Silicone Tape

8911

Application Ideas

- Transparent splicing of silicone treated materials, including paper, liners and films.
- High temperature label protection.
- One hour photo lab splicing tape.
- Electrical insulation tape.
- Circuit board masking.
- Masking parts in an anodizing process.
- Masking edges of overlap seams in metal bonding process where excess epoxy (flash) flows onto tape. Clean-up is complete upon tape removal.
- Composite and metal bonding – this tape removes cleanly from stainless steel, anodized aluminum and glass after a four-hour bake cycle at 350°F (177°C).

Storage

Store under normal conditions of 60° to 80°F (15° to 27°C) and 40 to 50% R.H. in the original carton.

Shelf Life

To obtain best performance, use this product within 18 months from date of manufacture.

For Additional Information

To request additional product information or to arrange for sales assistance, call toll free 1-800-362-3550 or visit www.3M.com/industrialtape. Address correspondence to: 3M Industrial Adhesives and Tapes Division, Building 21-1W-10, 900 Bush Avenue, St. Paul, MN 55144-1000. Our fax number is 651-778-4244. In Canada, phone: 1-800-364-3577. In Puerto Rico, phone: 1-787-750-3000. In Mexico, phone: 52-70-04-00.

Product Use

All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

Warranty and Limited Remedy

Unless stated otherwise in 3M's product literature, packaging inserts or product packaging for individual products, 3M warrants that each 3M product meets the applicable specifications at the time 3M ships the product. Individual products may have additional or different warranties as stated on product literature, package inserts or product packages. 3M MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. If the 3M product is defective within the warranty period, your exclusive remedy and 3M's and seller's sole obligation will be, at 3M's option, to replace the product or refund the purchase price.

Limitation of Liability

Except where prohibited by law, 3M and seller will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

3M

Industrial Business
Industrial Adhesives and Tapes Division
3M Center, Building 21-1W-10, 900 Bush Avenue
St. Paul, MN 55144-1000



Recycled Paper
40% pre-consumer
10% post-consumer

Printed in U.S.A.
©3M 2003 70-0709-4835-4 (9/03)