

July, 2009

# 3M™ Scotch® Transparent Film Tape 605

### **Product Description**

Scotch® Transparent Film Tape 605 is designed for various light-duty packaging applications such as attaching, mending, gift wrapping, holding and L-Clips. This product offers good performance over broad temperature ranges; specifically in cold and damp applications.

### **Product Features**

- Conformable backing.
- Edge tear and split resistant.
- Good aging in sunlight or fluorescent lighting.
- Smooth unwind.
- Quick and easy in application.
- Easy to read through.
- Good cold temperature stability.
- FDA approved for indirect food contact.



### **Technical Information Note**

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

## **Typical Physical Properties**

Property	Values		Method
Color	Clear		
Total Tape Thickness	0.063 mm	2.5 mil	ASTM D3652
Backing Thickness	0.041 mm	1.6 mil	ASTM D3652
Backing	Biaxially oriented polypropylene film		
Adhesive	*Pressure sensitive acrylic.		
*Note	Requires no moisture, heat or solvent for activation.		

# **Typical Performance Characteristics**

Property	Values		Method	Substrate
Peel Adhesion	3 N/cm	27 oz/in	ASTM D3330	Stainless Steel
Longitudinal Tensile Strength	38.5 N/cm	22 lb/in	ASTM D3759	
Elongation at Break	57 %		ASTM D3759	

### **Available Sizes**

Property	Values	
Standard Roll Length	65.8 m	72 yd
Standard Width	9.5, 12.7, 19, 25.4 mm	3/8, 1/2, 3/4, 1 in
Core Size (ID)	76.2 mm	3 in

## **Storage and Shelf Life**

Store in a clean, dry place. Temperature of 40-80°F (4-26°C) and 40 to 50% relative humidity are recommended. To obtain best performance, use this product within 18 months from date of manufacture.

### **Trademarks**

Scotch is a registered trademark of 3M.

### References

Property	Values
3m.com Product Page	https://www.3m.com/3M/en_US/company-us/all- 3m-products/~/Scotch-Light-Duty-Packaging-Tape- 605-Cold-Temperature? N=5002385+3293242205&rt=rud
Safety Data Sheet (SDS)	https://www.3m.com/3M/en_US/company-us/SDS-search/results/? gsaAction=msdsSRA&msdsLocale=en_US&co=ptn&q=60

### **ISO Statement**

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001 standards.

### 3M™ Scotch® Transparent Film Tape 605

#### Information

**Technical Information:** The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.



