

June, 2003

## 3M™ Tartan™ Label Protection Tape 3765

### Product Description

Tartan™ Label Protection Tape 3765 is a utility-grade label protection tape with a clear, strong, moisture-resistant film backing and a clear adhesive that holds well to many treated and finished surfaces. This tape may be used for attachment and preservation of identifying labels in shipping, storage, and manufacturing applications.



### Product Features

- Adheres instantly to a variety of surfaces.
- Edge tear and split resistance.
- Conformable backing.
- Good adhesion at 40°F (4°C).
- Complies with environmental consideration of ASTM D1974-92.
- Acrylic adhesive stays clear and is UV-resistant.
- Clear protection of labels from smudging, splashing, and tearing.
- This tape holds well up to 220°F (104°C) and in cold temperatures.
- Clear surface allows sharp bar code read.
- A great choice for outdoor protection applications.

# 3M™ Tartan™ Label Protection Tape 3765

## Technical Information Note

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

## Typical Physical Properties

Property	Values		Method
Color	Clear		
Total Tape Thickness	0.038 mm	1.5 mil	ASTM D3652
Backing	Biaxially oriented polypropylene film		
Adhesive	Pressure sensitive acrylic		
*Note	Utility-grade Tartan™ Tapes have physical properties that may vary over a broad range.		

## Typical Performance Characteristics

Property	Values		Method	Substrate
Peel Adhesion	2.4 N/cm	22 oz/in	ASTM D3330	Stainless Steel
Longitudinal Tensile Strength	35 N/cm	20 lb/in	ASTM D3759	
Transverse Tensile Strength	52.5 N/cm	30 lb/in	ASTM D3759	
Elongation at Break	119 %		ASTM D3759	

# 3M™ Tartan™ Label Protection Tape 3765

## Available Sizes

Property	Values	
Standard Roll Length	132 m	144 yd
Standard Width	72, 96, 120, 144 mm	
Core Size (ID)	76.2 mm	3 in

## Storage and Shelf Life

Store in a clean, dry place. Temperature of 40-80°F (4-26°C) and 40-50% relative humidity are recommended.

## References

Property	Values
3m.com Product Page	<a href="https://www.3m.com/3M/en_US/company-us/all-3m-products/~/Tartan-Label-Protection-Tape-3765?N=5002385+3292095717&amp;rt=rud">https://www.3m.com/3M/en_US/company-us/all-3m-products/~/Tartan-Label-Protection-Tape-3765?N=5002385+3292095717&amp;rt=rud</a>
Safety Data Sheet (SDS)	<a href="https://www.3m.com/3M/en_US/company-us/SDS-search/results/?gsaAction=msdsSRA&amp;msdsLocale=en_US&amp;co=ptn&amp;q=3765">https://www.3m.com/3M/en_US/company-us/SDS-search/results/?gsaAction=msdsSRA&amp;msdsLocale=en_US&amp;co=ptn&amp;q=3765</a>

## ISO Statement

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001 standards.

## For Additional Information

To request additional product information or to arrange for sales assistance, call toll free 1-800-362-3550 or visit [www.3M.com/packaging](http://www.3M.com/packaging). Address correspondence to: 3M Industrial Adhesives and Tapes Division, Building 21-1W-10, 900 Bush Avenue, St. Paul, MN 55144-1000. Our fax number is 651-778-4244. In Canada, phone: 1-800-364-3577. In Puerto Rico, phone: 1-787-750-3000. In Mexico, phone: 52-70-04-00.

# 3M™ Tartan™ Label Protection Tape 3765

## Information

**Technical Information:** The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

**Product Selection and Use:** Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

**Warranty, Limited Remedy, and Disclaimer:** Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

**Limitation of Liability:** Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

# 3M™ Tartan™ Label Protection Tape 3765



3M United States  
3M Center  
St. Paul, MN 55144-1000  
800-362-3550  
[www.3M.com](http://www.3M.com)

Please recycle.  
© 3M 2020. All Rights Reserved.

The brands listed above are trademarks of 3M