

3M™ Conformable Sound Management Film 9343

Product Description

3M™ Conformable Sound Management Film 9343 is designed for the reduction of noise, vibration, squeaks, and rattles in automotive interior applications. The currently available materials for these applications such as flocked cloths and felts are not as elastic, thereby limiting their use to flat surfaces only.

Product Features

- Bonded to an automotive interior component prevents noise and wear by isolating adjacent parts.
- Easily conforms to irregular and curved surfaces meeting a need for sound management that current materials cannot offer.
- Bond strength is dependent upon the amount of adhesive-to-surface contact developed. Firm application pressure develops better adhesive contact and thus improves bond strength.
- To obtain optimum adhesion, the bonding surfaces must be clean, dry and free of oil and dust. Typical cleaning solvents are isopropyl alcohol and water (rubbing alcohol) or heptane.*
- Initial tape application to surfaces at temperatures below 50°F (10°C) is not recommended because the adhesive becomes too firm to adhere readily. However, once properly applied, low temperature holding is generally satisfactory.

*Note: Carefully read and follow the manufacturer's precautions and directions for use when working with solvents.



Technical Information Note

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Typical Physical Properties

Property	Values		Method	Test Condition
Color	Black			
Total Tape Thickness	0.43 mm	17 mil	ASTM D3652	
Backing	Non-woven			
Adhesive	Acrylic			
Liner Thickness	0.15 mm	6 mil	ASTM D3652	
Flammability Test	Pass		FMVSS 302	
Fog Test	91 %			90°C

Tabor Abrasion

Dry (2000 cycles) - No wear through

Wet (1000 cycles) - No wear through

Heat Aged (14 days @ 82°C [180°F]) for 2000 cycles) - No wear through

Typical Performance Characteristics

Property	Values		Method	Substrate
Peel Adhesion	3 N/cm	27 oz/in	ASTM D3330	Stainless Steel
Tensile Strength	8.8 N/cm	80 oz/in	ASTM D3759	
Elongation at Break	400 %		ASTM D3759	
Temperature Use Range	-34 to 121 °C	-30 to 250 °F		

90° Peel Adhesion		Dwell/Cure Time	Substrate
9.19 N/cm	83 oz/in	20 min @ Room Temperature	ABS
11.97 N/cm	109 oz/in	72 hr @ Room Temperature	ABS
6.12 N/cm	56 oz/in	20 min @ Room Temperature	Polypropylene (PP)
7.67 N/cm	70 oz/in	72 hr @ Room Temperature	Polypropylene (PP)
6.16 N/cm	56 oz/in	20 min @ Room Temperature	Paint
9.57 N/cm	86 oz/in	72 hr @ Room Temperature	Paint

Property: 90° Peel Adhesion

Backing: Aluminum Foil

notes: 12 in/min (300 mm/min)

3M™ Conformable Sound Management Film 9343

Available Sizes

Property	Values	
Standard Roll Length	33 m	36 yd

Storage and Shelf Life

Store under normal conditions of 72°F (22°C) and 50% R.H. in the original carton.
To obtain best performance, use this product within 12 months from date of manufacture.

References

Property	Values
3m.com Product Page	https://www.3m.com/3M/en_US/company-us/all-3m-products/~ /3M-Conformable-Sound-Management-Film-Tape-9343?N=5002385+3293242544&rt=rud
Safety Data Sheet (SDS)	https://www.3m.com/3M/en_US/company-us/SDS-search/results/?gsaAction=msdsSRA&msdsLocale=en_US&co=ptn&q=9343

ISO Statement

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001 standards.

Information

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

