

January, 2011

# 3M™ Scotch® Security Message Box Sealing Tape 3779

## **Product Description**

Scotch® Security Message Box Sealing Tape 3779 is an industrial packaging tape used for box sealing specifically where security of the carton contents is a concern. The printed design along with the message make it easier to note when a package has been opened. Additionally, this product has a conformable backing and a consistent pressure sensitive hot melt adhesive system. This time-proven construction assures a reliable performance in a range of environments and applications.

#### **Product Features**

- Clear with red printed diagonal lines and message, "Check Seal Before Accepting".
- Diagonal lines and printed message makes it easier to notice when a package has been opened and resealed.
- Adheres instantly to a variety of surfaces.
- Conformable backing with edge tear and split resistance.
- Good adhesion to fiberboard.
- Reliable closures.



## **Technical Information Note**

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

## **Typical Physical Properties**

Property	Values		Method
Color	Clear with red printed message		
Total Tape Thickness	0.048 mm	1.9 mil	ASTM D3652
Backing Thickness	0.030 mm	1.2 mil	ASTM D3652
Backing	Biaxially oriented polypropylene film		
Adhesive	Pressure sensitive hot melt rubber-resin		
Holding Power to Fiberboard	3,500+ min		ASTM D3654

## **Typical Performance Characteristics**

Property	Values		Method	Substrate
Peel Adhesion	43.8 N/100mm	40 oz/in	ASTM D3330	Stainless Steel
Elongation at Break	160 %		ASTM D3759	
Note	Based on limited production. As sufficient production data is gathered, a revised data sheet will be issued.			

Tensile Strength		Test Condition
385 N/100mm	22 lb/in	Machine Direction
771 N/100mm	44 lb/in	Cross Direction

Property: Tensile Strength Method: ASTM D3759

#### **Available Sizes**

Property	Values	
Standard Length	100, 914 m	109, 1000 yd
Standard Width	48, 72 mm	1.9, 2.8 in
Core Size (ID)	76.2 mm	3 in

## Handling/Application Information

## **Application Techniques**

An extensive line of application equipment including hand-held manual dispensers and semi-automatic and fully automatic equipment is available. Application of Scotch® Security Message Box Sealing Tape 3779 is most easily accomplished at room temperature. At colder temperatures, approaching 32°F (0°C), the adhesive becomes more firm. Once applied, Scotch® Tape 3779 performs well throughout the normal temperature ranges typically encountered by packaged products in shipping and storage environments.

## Storage and Shelf Life

Store in a clean, dry place. Temperature of 40-80°F (4-26°C) and 40 to 50% relative humidity are recommended. To obtain best performance, use this product within 18 months from date of manufacture.

#### **Trademarks**

Scotch is a registered trademark of 3M.

#### References

Property	Values
3m.com Product Page	https://www.3m.com/3M/en_US/company-us/all-3m-products/~/Scotch-Security-Message-Box-Sealing-Tape-3779?N=5002385+3293242022&rt=rud
Safety Data Sheet (SDS)	https://www.3m.com/3M/en_US/company-us/SDS-search/results/? gsaAction=msdsSRA&msdsLocale=en_US&co=ptn&q=3779

#### **ISO Statement**

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001 standards.

#### Information

**Technical Information:** The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.